









AVENUE^{Patented}

metalfire

Technical Document

AVENUE+ MF 700-60 GHE 2SR

Dimensions (mm)

- combustion opening WxDxH: 744x336x590
- external WxDxH: 828x444x970
- diameter flue: Ø100/150 or (*) Ø80/125

TECHNICAL DATA

- Gascat: I2E+, I2E, I2H, I2L, I2ELL
 - ECOLABEL: A
 - load input: 6,50 kW
 - load output: 5,80 kW
 - efficiency capacity: 90,1 %
 - type of gas/pressure: G20/G25
- Gascat: I3B/P, I3+
 - ECOLABEL: B
 - load input: 5,80 kW
 - load output: 4,70 kW
 - efficiency capacity: 81,2 %
 - type of gas/pressure: G30/G31
- Appliance type: C11,C31,C91
C12,C32,C42,C52,C82
- Weight: 100 kg
- Convection air inlet: min350cm2 (2xØ150)
- Convection air outlet: min350cm2 (2xØ150)

SPECIFICATIONS

- Only available with ceramics wood logs
- Ionization-protected pilot-flame
- Radiographic remote controle with thermostatic mode
- Inside finishing: heat-resistant black point
- Gas/electrical connections at the left side (optional right side)

OPTIONS

- interior finishing: ORIGINAL (ribbed cast iron)
- Standard (steel)

First aid and technical support:

- support@metalfire.eu
- +32 (0)9 261 50 57

scale 1:20

www.metalfire.eu EN 613 CE

General dimensional tolerances up to 6mm
Metalfire preserves the right to modify specifications without previous notice

Sheet
1/3

WITHOUT FINISHING FRAME

AVENUE_{Patented}

metalfire

Technical Document

AVENUE+ MF 700-60 GHE 2SR

Prescribed insulation thickness (mm)

Combustable finishing material

Metalfire recommended
Promasil 1100L
(TC=0,081 W/mK)

A = 25mm

Non-combustable finishing material

non-combustable
materials
structural building items
EXCLUDED e.g load bearing walls

A = 0mm

TC=thermot conductivity

TC=non-combustable

Table: AVENUE+ MF 700-60 GHE 2SR

Installation dimensions (mm)

P	Q	R	S	T	Z
747	590	854	850	616	NA

First aid and technical support:
- support@metalfire.eu
- +32 (0)9 261 50 57

scale 1:20

Rev.



www.metalfire.eu

EN 613

CE

General dimensional tolerances up to 6mm
Metalfire preserves the right to modify specifications without previous notice

Sheet
2/3




Electrical/gas control unit

Standard connected with 1m flexible tube.

Optional: connected on right side and/or with an additional 1m tube(AT ORDER)

FORESEE ENOUGH AIR FLOW FOR COOLING



Combustable finishing material

Insulation

Insulation thickness = > see table

WITH FINISHING FRAME 90/10

AVENUE_{Patented}

metalfire

Technical Document

AVENUE+ MF 700-60 GHE 2SR

Prescribed insulation thickness (mm)

Combustable finishing material

Metalfire recommended
Promasil 1100L
(TC=0,081 W/mK)

A = 25mm

Non-combustable finishing material

non-combustable
materials
structural building items
EXCLUDED e.g load bearing walls

A = 0mm

TC=thermot conductivity

TC=non-combustable

Table: AVENUE+ MF 700-60 GHE 2SR

Installation dimensions (mm)

P	Q	R	S	T	Z
747	590	854	850	616	NA

First aid and technical support:
- support@metalfire.eu
- +32 (0)9 261 50 57


scale 1:20

Rev.


www.metalfire.eu EN 613 CE

General dimensional tolerances up to 6mm
Metalfire preserves the right to modify specifications without previous notice

Sheet
3/3




Detail2
SCALE 1:4



Combustable finishing material

Insulation

Insulation thickness = > see table



Electrical/gas controle unit

Standard connected with 1m flexible tube.

Optional: connected on right side and/or with an additional 1m tube(AT ORDER)

FORESEE ENOUGH AIR FLOW FOR COOLING

